

# ZK1515

## All in One Biometric Smart Pos Terminal



### Features

- Power-efficient Intel® Celeron® J1900 2.0 GHz Quad-Core processor;
- 15" Bezel-Free true-flat display with PCAP touch;
- Multiple I/O interfaces for peripherals;
- Fanless design, less heat, longlasting performance, low consumption;
- Standard with 2G RAM and 32G SSD;
- Standard with 8C high-definition digital tube;
- Optional 3 tracks MSR, attached VFD&12.1" customer display;
- Faster installation and maintainability;

### Optional



Magnetic Stripe Card Reader



2<sup>nd</sup> LCD Display Screen



Barcode Scanner



Mifare/RFID



Thermal Printer



Cash Drawer



VFD Customer Display



Fingerprint

# Specifications

|                                  |   |
|----------------------------------|---|
| Model Name                       | ZK1515  |
| <b>System</b>                    |   |
| Processor                        | Intel® Celeron J1900 Quad-Core processor (2.0 GHz)                  |
| System Memory                    | 2GB Standard, DDR3L 1333MHz (Max.8GB)                               |
| Storage Device                   | 32GB SSD Standard, 1*2.5" HDD & 2.5" SSD                            |
| OS Supported                     | Windows 7, Windows 8, Windows 10 IoT Enterprise, POS Ready 7, Linux |
| Audio                            | Realtek ALC662  |
| <b>Display and Touch</b>         |   |
| Type                             | 15" TFT LCD, LED Backlight  |
| Resolution                       | 1024×768  |
| Touch Screen                     | Projected Capacitive Touch Screen                                   |
| <b>External I/O Ports</b>        |   |
| VGA                              | 1*DB-15   |
| USB                              | 4*USB 2.0 & 2*USB 3.0   |
| Serial                           | 1*RS232 (Max.4pcs)  |
| LAN                              | 1*RJ45  |
| Audio                            | 1*Line-out  |
| <b>Power</b>                     |   |
| Power Supply                     | Adaptor 12V DC 5A   |
| <b>Physical Environment</b>      |   |
| Operating Temperature            | 0°C ~ 35°C at 20% - 80% Humidity                                    |
| Storage Temperature              | - 20°C ~ 55°C at 20% - 80% Humidity                                 |
| Dimensions (W×H×D)               | 358*368*222 mm  |
| Packing Dimensions               | 405*430*260 mm  |
| Net Weight                       | 5.5kg   |
| Packing Weight                   | 6.5kg   |
| Certification                    | CE FCC  |
| Color                            | Black   |
| <b>Options &amp; Peripherals</b> |   |
| 2nd Display                      | 12.1" TFT LCD   |
| Customer Display                 | 20 Columns × 2 Lines  |
| MSR                              | 3 Tracks  |
| Fingerprint                      | USB fingerprint reader (SLK20R)                                     |



ZKTECO CO.,LTD.  
[www.zkteco.com](http://www.zkteco.com)  
 E-mail: [sales@zkteco.com](mailto:sales@zkteco.com)

© Copyright 2017. ZKTECO CO.,LTD. ZKTECO Logo is a registered trademark of ZKTECO or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.

