

SF-NVR6432-4K16P

NVR Recorder for IP
32Ch video / 16 PoE Port(s)
Max Resolution 8.0 Mpx /
Compression H.265+
Bandwidth 256 Mbps
Outputs 4K HDMI & VGA
Space for 4 hard disks



Safire
NVR Recorder for IP
32 CH
256 Mbps bandwidth supported
Maximum resolution 8 Megapixel
Compression H.265+ / H.265 / H.264+ / H.264
Alarms
VGA and HDMI 4K output
IP Dual Stream Access
Mouse
Space for 4 HDD
16 PoE ports IEEE802.3af/at
WEB,(SCC) and Smartphone interface
ONVIF Compatible

Specifications

| | |
|-----------------------------------|-------------------------------------------------------------------------|
| Brand | Safire |
| Inputs for IP cameras | LAN port up to 36 channels |
| Power over Ethernet | 16 port Switch PoE IEEE802.3af/at (max. 200 W) |
| IP compatible cameras | SAFIRE (native protocol), ONVIF |
| Bidirectional audio | 1 input / 1 RCA output |
| Video outputs | 1 HDMI 4K, 1 VGA |
| Video compression format | H.265+ / H.265 / H.264+ / H.264 |
| Display resolution | 3840x2160, 2560x1440, 1920x1080, 1280x1024, 1280x720, 1024x768 |
| Total bandwidth | 256 Mbps downstream / 160 Mbps upstream |
| Main Stream recording | 8MP/6MP/5MP/4MP/3MP/1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF |
| Simultaneous multifunction | Pentaplex: Live, Recording, Playback, Backup and Remote Access |
| Alarms | 16 Inputs / 4 Relay NO/NC |
| Recording method | Manual, programmed, motion detection, alarm |
| External Backup | USB memory / HDD USB / CD-RW USB / DVR-RW USB |
| Internal memory | 4 SATA HDD 3.5" of up to 6 TB (not included) |
| Communication | RS485 (PTZ) / RS232 / 1 x USB 3.0 / 2 x USB 2.0 / 1 x RJ45 (Ethernet) |
| Remote access | Web browser, Safire Control Center Smartphone App and PC Software |
| Power supply | AC 100~240 V, 50/60 Hz |
| Dimensions / Weight | 70 (H) x 445 (W) x 390 (D) mm / 5.0 Kg (without HDD) |