

XS-CV201KA-F4N1

2 Megapixel bullet camera

PRO Range

1/2.7" CMOS Sensor 1080p

2.8 mm Lens

IR Illumination 80m

Audio with integrated microphone



X-Security

HDTVI, HDCVI, AHD and Analogue bullet camera

PRO Range

1/2.7" 2 Megapixel

HD 1080P (1920x1080)

HDCVI output

2.8 mm Lens

0 Lux - IR Range 80m

IR Cut

Audio with integrated microphone included

Weatherproof IP67

Specifications

Brand	X-Security
Range	1080p PRO
Image sensor	1/2.7" CMOS
Resolution	1080p (1920x1080) at 30 FPS
Video output	1 x BNC HDCVI/CVBS (CVBS with DIP switch)
Minimum illumination	Color 0.02 Lux / B/W 0 Lux IR 80m
Basic functions	OSD Menu
Configurable OSD functions	DWDR, 2D-NR, HLC, BLC, AGC
Lens	2.8mm (H:87.5°)
Audio	Integrated microphone
Power supply	DC 12 V / 5.3 W max.
Degree of protection	Weatherproof IP67
Temp. operation	-40° C ~ +60° C
Dimensions	198.9mm (d) × 76.2mm (h) × 80.2mm (w)
Weight	0.27 Kg