

XS-DM885SA-F4N1

2 Megapixel dome camera

PRO Range

1/2.8" CMOS Sensor 1080p

2.8 mm Lens

IR Illumination 50m

Audio with integrated microphone



X-Security

HDTVI, HDCVI, AHD and Analogue dome camera

PRO Range - 1/2.8" 2 Megapixel - HD 1080P (1920x1080)

Output 4in1

2.8 mm Lens

High sensitivity Starlight

0 Lux

IR Range 50m

IR Cut

Audio with integrated microphone included

Weatherproof IP67

Specifications

Brand	X-Security
Range	1080p PRO
Image sensor	1/2.8" CMOS
Resolution	1080p (1920x1080) at 30 FPS
Video output	1 x BNC HDTV / HDCVI / AHD / CVBS (CVBS with DIP switch)
Minimum illumination	Color 0.005 Lux / B/W 0 Lux IR 50m
Basic functions	OSD Menu
Configurable OSD functions	DWDR, 2D-NR, HLC, BLC, AGC
Lens	2.8mm (H:87.5°)
Audio	Integrated microphone
Power supply	DC 12 V / 4.7 W max.
Degree of protection	Weatherproof IP67
Temp. operation	-40° C ~ +60° C
Dimensions	94 (H) x 106 (Ø) mm
Weight	440 g