


# Odyssey 2

## Polycarbonate External Sounder & Strobe Unit

Texecom is proud to introduce the revolutionary Odyssey 2. With environmentally sealed microprocessor technology, twin piezo sounders and triple tamper detection, exceptional performance is guaranteed. Incorporating a 3mm polycarbonate housing as standard, the Odyssey 2 is the perfect choice for any professional installation.

### Outstanding features:

- 115db Volume
- IP65 Sealed Electronics
- Patented Safety Engineer Hold-off Mode
- Screw, Lid & Wall Tamper
- Patented Safety Engineer Hold-off Mode
- Twin Alternating LEDs
- Twin Piezo Sounders
- Advanced Microprocessor Technology
- Strobe Tube Saver
- Selectable SAB/SCB Mode
- Low Current Mode
- Polycarbonate Construction
- EN 50131 Grade 3



**Texecom**  
Designed to Perform

# Odyssey 2



## Patented Engineer Hold-off Mode

Installation and maintenance is made quick, simple and safe by a revolutionary patented safety engineer hold-off mode. On power-up the hold-off mode is automatically enabled, preventing the unit from sounding until the tamper circuit is secure. This enables "one trip up the ladder" installation. Hold-off mode can be re-invoked at any time from the control panel, ensuring easy maintenance and verification.



## IP65 Sealed Electronics Module

The advanced electronic module of the Odyssey 2 is protected by a robust inner cover assembly with gasket seal. This increases protection from dust and moisture, sealing to IP65 rating which enables prolonged exposure to harsher environments without compromising performance or functionality.




## Triple Tamper Detection

Lid, wall and screw tamper detection is provided as standard. Texcom's proprietary wall tamper mechanism ensures maximum reliability with excellent responsiveness. Screw tamper provides the earliest possible indication of unauthorised access to the unit.

## Specifications

Supply Voltage:	13.7V (nominal)		
Current Drain			
Quiescent (inc charging):	15mA		
Strobe:	100mA		
Sounder:	SAB	LC	SCB
	405mA	190mA	30mA
Battery:	NiMh Stack, 7.2Vdc, 320mAh		
Strobe:	1W, 1Hz Flash Rate		
Dimensions:	382mm x 242mm x 76mm		
Packed Weight:	1600g (56oz) approx		



## European Standards

Safety: Conforms to European Union (EU) Low Voltage Directive (LVD) 73/23/EEC (amended by 93/68/EEC).

EMC: Conforms to European Union (EU) Electro-Magnetic Compatibility (EMC) Directive 89/336/EEC (amended by 92/31/EEC and 93/68/EEC).

Approved to BS EN 55022 Class B and BS EN 50130-4 : 1996.

PD 6662 & EN 50131-1 Grade 3 Environmental Class IV.

The CE mark indicates that this product complies with the European requirements for safety, health, environmental and customer protection.

Texcom products are protected by UK and International patents, trademarks and registered design rights.

UK Registered Design Number 2079735.

Odyssey is a trademark of Texcom Ltd. © 2009 Texcom Ltd. (LIT-0032)



Certificate Number: FM 35285



A20090326